

Original Research

The effect of power losses for agricultural tractor on tractive efficiency

Authors:**Hussein Abbas Jebur****Institution:**Department of Agricultural
Machines and Equipment,
College of Agriculture,
University of Baghdad,
Iraq.**Corresponding author:****Hussein Abbas Jebur****ABSTRACT:**

The present study was conducted to determine the effect of depths of plough at the farm by tractor on tractive efficiency and operation costs. The studied variables were two depths of plough (16-20 and 21-24cm), three equipment plough (disk, chisel and sweep) and five different forward speeds. The average soil moisture content was (18.61%) and the soil texture was found to be silt-clay. The study was focused on the rate of power losses, fuel consumption, pull ratio, tractive efficiency and operation costs. The experiment was carried out by using split-split plot with complete randomized block design, three replicates. The obtained results, for the range of tests, showed that the use of disk plough superposed the chisel plough and sweep plough, in recording lowest rate of fuel consumption (16.016 l/h). While the sweep plough superposed the chisel plough and disk plough, in recording lowest rate of power losses (10.13 kW) and higher rate of tractive efficiency (75.17%). The forward speed (8.14 km/h) superposed in recording higher rate of pull ratio (0.482) and lowest rate of operation costs 23592 ID/ha. While the first forward speed (2.72 km/h) was superior on other forward speed in recording lowest rate both of fuel consumption (13.80 l/h) and power losses (1.99 kW), and higher rate of tractive efficiency (75.49%), in the meantime, the depths of plough (16-20cm) recorded lowest rate of fuel consumption (16.97 l/h), power losses (9.64 kW), operation costs 23903ID/ha and higher rate both of tractive efficiency (75.36%) and pull ratio (0.441).

Keywords:

Costs, Chisel, Plough, Power, Sweep.

Abbreviation: **FS:** Forward speed (km/h); **FC:** rate of fuel consumption (l/h); **A:** Rolling resistance for the working unit (kN); **B:** The recording pull by using implement (kN); **Ndp:** Net drawbar pull (kN); **P_d:** Drawbar power (kW); **P_{sl}:** Power consumed by slip (kW); **P_{dp}:** Drawbar power (kW); **P_{rr}:** Rolling resistance power (kW); **T_e:** Cost per hour of operation (ID/h); **Efc:** Effective Field capacity (ha/h); **Oc:** Operation costs (ID/ha).

Article Citation:**Hussein Abbas Jebur**

The effect of power losses for agricultural tractor on tractive efficiency

Journal of Research in Ecology (2018) 6(1): 1492-1500**Dates:****Received:** 09 Jan 2018 **Accepted:** 13 Feb 2018 **Published:** 25 Mar 2018**Web Address:**[http://ecologyresearch.info/
documents/EC0538.pdf](http://ecologyresearch.info/documents/EC0538.pdf)

This article is governed by the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/4.0>), which gives permission for unrestricted use, non-commercial, distribution and reproduction in all medium, provided the original work is properly cited.

INTRODUCTION

The farm tractor is the key source of power on the farm, which meets these requirements of the required power but there are diversity and significant difference of existing tractors in the agricultural field in many countries of the world, including Iraq. The efficiency and capacity of the agricultural tractor is determined according to the type and nature of the work (towing, loading) with the various agricultural machines in a number of well-studied calibrations in accordance with the suitability of the tractor and the nature of the agricultural land according to its dimensions on the ground; and also on the basis of the agricultural equipments associated with it. This in turn encourages states to expand the use of units of agricultural mechanization to provide human capital and raising the quality of agricultural products, but the development did not seem obvious unless in the current century. Drawbar work is known through pull force and speed. Therefore, the tractor cannot convert the full energy of fuel into useful work at the drawbar. Virtually, most of the potential energy is lost in transforming chemical energy into mechanical energy, along with losses from the engine through the drivetrain and finally through the tractive device. Research showed that about "20% to 55%" of the available tractor energy is exhausted at the tractive device (Wulfsohn, 1988). Efficient traction of tractors includes; maximizing the fuel efficiency of the engine and propulsion system, maximizing the tractive priority of the traction devices, and selecting an optimum forward speed for a given tractor-implement system (Zoz and Grisso, 2003).

Al-Aridhee (2011) found that fuel consumption may fit directly proportional with increasing depth, and attributed that to the increased depth requiring, more

work and more fuel consumption. Aday *et al.* (2008) concluded that higher tractor forward speed may give the least amount of fuel consumption per unit area because high speed leads to a reduction in the period of time to complete the unit area as well as losing the tractor ability optimally in the slow speeds. Tillage speed has significant impact on the traction force and increasing tillage speed lead to the increase of traction force, and on this, the foundation of the primary speed recorded 3.35 km/h as the least traction force, reaching 6.149 kN while third speed reached 6.55 km/h and the highest traction force, reached to 7.821 kN. The reason attributed to that increase accelerated tillage led to further accelerate in soil compounds and increase the energy given to the soil as a result of increased speed (Hilal, 2010). High tractive efficiency was obtained at a lower of slip in the range of 10–20%. Higher tractive efficiency occurred at a pull ratio of 0.40–0.50. Abbaspour *et al.* (2007) reported that the agricultural tractors consume about 20 percentage of total energy, required for a farm. Therefore optimizing performance of agricultural tractors could bring energy losses down. Younis *et al.* (2010) indicated that the performance of drawbar test has measured the following data: forward speed, fuel consumption, the equivalent forward speed and drawbar pull. This research was conducted to facilitate the task of selecting the suitable tractor with the implement. The study aims at evaluating the impact of the traveling speed and depths of plough on tractor performance parameters, namely power losses, tractive efficiency and fuel consumption.

MATERIALS AND METHODS

The experimental study was carried out at the college of agricultural-University of Baghdad. This

Table 1. Mechanical analysis of the experimental soil

S. No	pH	Electrical conductivity (ds/m)	Soil penetration resistance (kPa)	Porosity (%)	Bulk density (gm/cm ³)	Soil type	Soil texture (%)		
							Clay	sand	silt
1	7.52	8.69	4.88	41.35	2.56	S.C.L	31.7	58.1	2.10

paper presents the results of evaluation of the effect of depths of plough and different forward speeds on traction parameters and performance of an agricultural tractor, under field working conditions, in silt-clay loam soil. The variable depths of plough (16-20 and 21-24cm and forward speeds (from 2.72 to 8.14 km/h) were used. The mechanical analysis of the soil is shown in Table 1. The following materials and methods were used

A. Descriptions of tractors and implements:

Tractors

New Holland tractor model WD2*80-66 s NH, 80 hp-59.66 kW), and IMT-285 tractor (75 hp-55.93 kW).

Sweep plough

A local manufacture (1 board).

Disk plough

A local manufacture "State company for mechanical industries", Model PAM, type mounted three point hitch, Number of disks (3), Type of plate (standard), total working width of cut (90cm) and total weight (380 kg).

Chisel plough

A local manufacture "State company for mechanical industries", total width of 170cm, 9 boards.

B. Measuring instruments

Spring dynamometer and Fuel consumption apparatus.

C. Parameter measurement and determination:

Forward speed (FS)

The forward speed was calculated as follows:

$$FS = \frac{x}{t} \times 3.6 \quad (\text{Macmillan, 2002})$$

Fuel consumption (FC)

The fuel consumption was calculated as follows:

$$FC = \left(\frac{V}{t}\right) \times 3.6 \quad (\text{Macmillan, 2002})$$

Pull force

The draft force of the tractor was measured by using a spring dynamometer. The attached with a hori-

zontal chain between two tractors to measure the draft force. Two wheel drive tractor (IMT-285), was used as a rear (towed) on which the implement was mounted; whereas the front tractor (New Holland) was used to pull the towed tractor with the attached implement through the spring dynamometer. The towed tractor was working on the neutral gear while the implement that was in the operating position. On the same field, the implement was lifted out of the ground and the rear tractor was pulled to record the rolling resistance (A), then the drawbar pull (B) was calculated as follow:

During the operation the following measurement were obtained:

Drawbar power:

$$P_{dp} = NDP \times FS / 3.6 \quad (\text{Younis and EL-Said, 2009})$$

Power consumed by rolling resistance (P_{rr}):

$$P_{rr} \text{ (kW)} = \text{rolling resistance (kN)} \times FS \text{ (km/h)} / 3.6$$

Pull ratio:

$$\text{Pull ratio} = \frac{\text{Net drawbar pull (kg)}}{\text{Weight on rear wheel (kg)}} \quad (\text{Zoz and Grisso, 2003})$$

Power consumed by slip (P_{sl}):

$$P_{si} = [P_{db} + P_{rr}] \times \frac{S}{100 - S} \quad (\text{Younis and EL.Said, 2009})$$

Tractive efficiency

$$\eta_{TE} = \frac{\text{Output power}}{\text{Input power}} \times 100 \Rightarrow \frac{\text{Drawbar power}}{\text{Axle power}} \times 100 \quad (\text{Sharma and Mukesh, 2010})$$

Effective Field capacity (E_{fc})

$$\text{Effective Field Capacity} = \frac{1}{\text{effective total in hours} \dots \text{ha. h}^{-1}} \dots \text{required per feddan} \quad (\text{Liljedahl et al., 1989})$$

Operation costs

$$T_i = \left(\frac{C}{h}\right) \left(\frac{1}{L} + \frac{i}{2} + a + r\right) + (1.2 P.S.f) + \frac{m}{144} \dots I.D / h \quad (\text{Awady, 1987})$$

So equation becomes. Cost per unit work (O_c) = Hourly cost "T_i" / Effective Field capacity (E_{fc}).

Table 2. Effect of the forward speed, depths of plough and equipment on fuel consumption (l/h)

S. No	Characters studied		Fuel consumption (FC), l/h					Average depths of plough (cm)
			Interaction between, depths, equipment and speed					
	Equipment of plough	Depths of plough (cm)	Forward speed km/h					
Transactions		8.14	6.43	4.31	3.23	2.72		
1	Disk	16-20	19.130	17.110	14.730	13.130	12.520	16.97
2	Chisel		19.363	17.730	15.120	13.630	12.820	
3	Sweep		21.233	18.120	15.640	14.750	13.930	
1	Disk	21-24	20.850	18.540	15.216	14.623	14.230	17.29
2	Chisel		21.250	19.112	16.920	15.327	14.422	
3	Sweep		21.662	19.653	16.851	15.841	14.846	
L.S.D = 0.05			0.0243±0.001					0.0032
Average of speed			20.58	18.38	15.75	14.55	13.80	
L.S.D = 0.05			0.0053±0.0004					
Average equipment of plough								
			Sweep	Chisel		Disk		
			17.252	16.569		16.016		
L.S.D = 0.05			0.0032±0.0001					

RESULTS AND DISCUSSION

This experiment was conducted in the field in order to evaluate a precision performance the tractor and implements, and also to determine the best working engineering performance parameters for the machine unit.

Fuel Consumption (FC) l/h

Results illustrated in Table 2 shows the effect of forward speed, depths of plough and equipment and their overlaps on the fuel consumption and is illustrate in Table 2. As seen from the table, the increase of the forward speed (2.72, 3.23, 4.31, 6.43 and 8.14 km/h), increased FC (1380, 18.38, 15.75, 14.55 and 20.58l/h) respectively with an average of 32.94%. The reason is that the tractor ability does not show optimally at slow velocities. Therefore, waste exists in energy. These results are consistent with the ones obtained by Kassari (2011) and Jebur (2016). The high velocities need a short time period to complete unit area according to the results of Khalilian *et al.* (1988). The same table shows

that increasing depths of plough has increased the fuel consumption with the ratio of 1.85%. This is because the increase in depth leads to increasing rolling resistance to penetrate and wheel slip; therefore, the tractor consumes more fuel to overcome this influence. These results are consistent with Khorshid (2016). Also the results in the Table 2 illustrated that the use of disk superposed the chisel plough and sweep plough, in recording lowest FC (16.016 l/h). The reason may be because of consuming less amount of power. These results are consistent with the ones obtained by Khader (2008). So the Table 2 indicate that the interaction between equipment, forward speed and depths of plough were significant on the FC, whereas the triple overlap between the forward speed 2.72 km/h, disk plough and depths of plough 16-20cm led to obtain the lowest FC and was found to be 12.52 l/h, while the highest FC was 21.662 l/h resulting from the overlap of the sweep plough, depths of plough 21-24cm and traveling speed 8.14 km/h as.

Table 3. Effect of the forward speed, depths of plough and equipment on pull ratio

S. No	Characters studied		Pull ratio					Average depths of plough (cm)
	Transactions	Interaction between, depths, equipment and speed	Forward speed km/h					
	Equipment of plough	Depths of plough (cm)	8.14	6.43	4.31	3.23	2.72	
1	Disk	16-20	0.533	0.497	0.457	0.419	0.392	0.441
2	Chisel		0.475	0.429	0.389	0.377	0.328	
3	Sweep		0.475	0.417	0.382	0.372	0.313	
1	Disk	21-24	0.483	0.471	0.423	0.384	0.349	0.399
2	Chisel		0.473	0.413	0.406	0.357	0.341	
3	Sweep		0.449	0.441	0.398	0.367	0.285	
L.S.D = 0.05			0.0948±0.003					0.0356
Average of speed			0.482	0.445	0.409	0.378	0.335	
L.S.D = 0.05			0.0389±0.001					
Average equipment of plough								
			Sweep	Chisel				Disk
			0.390	0.403				0.417
L.S.D = 0.05			0.0386±0.002					

Pull ratio

Results illustrated in Table 3 shows the effect of forward speed, depths and equipment and their overlaps on the pull ratio are illustrate in Table 3. As seen from the table, the increase of the forward speed (2.72, 3.23, 4.31, 6.43 and 8.14 km/h), increased pull ratio (0.335, 0.379, 0.409, 0.445 and 0.482) respectively. The same table shows that the increasing depths of plough, the pull ratio has decreased. Also the results in the Table 3 illustrate that the use of disk plough superposed the moldboard and chisel plough, in recording higher pull ratio (0.417). Also Table 3 shows that the interaction between equipment, forward speed and depths of plough were significant on the pull ratio, whereas the triple overlap between the forward speed 8.14 km/h, disk plough and depths of plough 16-20cm led to obtain the highest pull ratio was 0.533%, while the lowest pull ratio 0.285% resulting from the overlap of the sweep plough, depths of plough 21-24cm and traveling speed

2.72 km/h.

Power losses (kW)

The effect of forward speed, depths of plough and equipment, and their overlaps on the power losses are tabulated in Table 4. As seen from the table, the increase of the forward speed (2.72, 3.23, 4.31, 6.43 and 8.14 km/h), increased power losses (1.99, 4.43, 8.25, 14.75 and 22.54 kW) respectively with average of 91.17%. The reason may be attributed to the fact that one of the factors involved in the calculation of speed that led to increase of power losses. These results are consistent with the results obtained by Madlol and Jebur (2014). The same table shows that increasing of the depths of plough the power losses has increased from 9.64 to 11.15 kW, with a ratio of 13.54%. The reason is that the increase of depths of plough led to the increase of load on the tractor consequence increased energy consumption. These results are consistent with the results obtained by Zedan (2006). Also the results in the

Table 4. Effect of the forward speed, depths of plough and equipment on power losses (kW)

S. No	Characters studied		Power losses (kW)					Average depths of plough (cm)
	Transactions	Interaction between, depths, equipment and speed	8.14	6.43	4.31	3.23	2.72	
	Equipment of plough	Depths of plough (cm)						
1	Disk	16-20	22.27	13.90	7.64	4.09	1.84	9.64
2	Chisel		20.97	13.26	7.35	3.85	1.70	
3	Sweep		21.93	12.56	7.81	4.23	1.79	
1	Disk	21-24	25.17	17.34	9.37	4.90	2.43	11.15
2	Chisel		22.87	16.32	8.63	4.61	2.01	
3	Sweep		22.59	15.14	8.75	4.88	2.18	
	L.S.D = 0.05		1.2397±0.02					0.3736
Average of speed			22.54	14.75	8.25	4.43	1.99	
L.S.D = 0.05			0.5600±0.04					
Average equipment of plough								
			Sweep	Chisel	Disk			
			10.13	10.16	10.89			
L.S.D = 0.05			0.0628±0.005					

Table 4 illustrate that the use of sweep plough superposed the disk plough and chisel plough, in recording lowest power losses (10.13 kW). So Table 4 indicate that the interaction between equipment, forward speed and depths of plough were significant on the power losses, whereas the triple overlap between the forward speed 2.72 km/h, disk plough and depths of plough 16-20cm led to obtain the lowest power losses i.e., 1.84 kW.

Tractive efficiency (η_{TE})

Table 5 showed the effect of forward speed, depths of plough and equipment and their overlaps on the tractive efficiency. As seen from the table, the increase of the forward speed (2.72, 3.23, 4.31, 6.43 and 8.14 km/h), decreased tractive efficiency (75.49, 75.24, 74.33, 73.77 and 73.10%) respectively. This may be due to the losses in output power that come from both slip and rolling resistance. These results are consistent with the results obtained by Jebur (2015). The same table showed that with the increasing depths of plough, the

tractive efficiency has decreased from 75.36% to 73.41%. This may be due to the increased power losses. Also the results in the Table 5 illustrate that the use of sweep plough superposed the chisel and disk plough, in recording highest tractive efficiency (75.17)%. The reason may be because of recording highest average of drawbar power. So the Table 5 indicate that the interaction between equipment, forward speed and depths of plough were significant on the tractive efficiency, whereas, the triple overlap between the forward speed 2.72 km/h, sweep plough and depths of plough 16-20cm led to obtain the highest tractive efficiency of 77.22%, while the lowest tractive efficiency was 70.67% resulting from the overlap of the disk plough, depths of plough 21-24cm and traveling speed 8.14 km/h.

Operation costs (ID/ha)

Table 6 showed the effect of forward speed, depths of plough and equipment and their overlaps on the operation costs. As seen from the table, the increase of the forward speed (2.72, 3.23, 4.31, 6.43 and 8.14

Table 5. Effect of the forward speed, depths of plough and equipment on tractive efficiency (%)

S. No	Characters studied		Tractive efficiency (%)					Average depths of plough (cm)
	Transactions		Interaction between, depths, equipment and speed					
	Equipment of plough	Depths of plough (cm)	8.14	6.43	4.31	3.23	2.72	
1	Disk	16-20	73.624	74.231	74.856	75.431	75.843	75.36
2	Chisel		74.226	74.451	75.331	76.251	76.561	
3	Sweep		74.763	75.061	75.912	76.621	77.223	
1	Disk	21-24	70.670	71.456	71.810	73.583	73.647	73.41
2	Chisel		71.970	73.370	73.893	74.273	74.370	
3	Sweep		73.303	74.047	47.157	75.280	75.297	
L.S.D = 0.05			0.0249±0.001					0.3736
Average of speed			73.10	73.77	74.33	75.24	75.49	
L.S.D = 0.05			0.00623±0.0002					
Average equipment of plough								
			Sweep	Chisel	Disk			
			75.17	74.47	73.51			
L.S.D = 0.05			0.0521±0.005					

Table 6. Effect of the forward speed, depths of plough and equipment on operation costs (ID/ha)

S. No	Characters studied		Operation costs (ID/ha)					Average depths of plough (cm)
	Transactions		Interaction between, depths, equipment and speed					
	Equipment of plough	Depths of plough (cm)	8.14	6.43	4.31	3.23	2.72	
1	Disk	16-20	20745	23232	24365	26545	27745	23903
2	Chisel		20114	22851	24121	25654	27321	
3	Sweep		18684	21524	23654	25153	26841	
1	Disk	21-24	28117	29543	30126	30523	31724	29313
2	Chisel		27346	28258	29652	30325	31154	
3	Sweep		26548	27823	28563	29567	30434	
L.S.D = 0.05			1145.4±15.5					936.23±26.3
Average of speed			23592	25538	26747	27961	29203	
L.S.D = 0.05			1126.16±33.2					
Average equipment of plough								
			Sweep	Chisel	Disk			
			25879	26680	27266			
L.S.D = 0.05			961.31±62.3					

25538 and 23592 ID/ha) respectively. The reason may be attributed to the fact that increasing of practical

speed led to increase of effective field capacity. Therefore, the tractor costs decreased as a result of the reverse

km/h), decreased operation costs (29203, 27961, 26747, relationships between effective field capacity and tractor costs. These results are consistent with the results obtained by Mayfield *et al.* (1981). The same table shows that increasing depths of plough and operation costs have decreased from 23903ID/ha to 29313ID/ha. This may be due to the increased fuel consumption, therefore the operation costs increased. These results are consistent with those obtained by Al-Janobi (2000) and Jabour, (2010). Also the results in the Table 6 illustrate that the use of sweep plough superposed the chisel and disk plough, in recording lowest operation costs 25879 ID/ha. So the Table 6 indicate that the interaction between equipment, forward speed and depths of plough were significant on the operation costs, whereas the triple overlap between the forward speed 8.14 km/h, sweep plough and depths of plough 16-20cm led to obtain the lowest operation costs i.e., 18684ID/ha, while the highest operation costs was 31724ID/ha resulting from the overlap of the disk plough, depths of plough 21-24cm and traveling speed 2.72 km/h.

CONCLUSION

Increasing the forward speed in an increase in fuel consumption, power losses per unit area and a significant decrease in tractive efficiency, pull ratio and operation costs. Also increasing the depths of plough in a significant increase in power losses, operation costs and fuel consumption. The use of depths of plough 16-20cm produced the highest value (75.36%) of tractive efficiency, while the lowest value of tractor costs was 29313ID/ha. The sweep plough recorded highest value (75.17%) of tractive efficiency and lowest value (25879 ID/ha) of operation costs.

REFERENCES

Abbaspour-Gilandeh Y, Omid M and Keyhani A. 2007. Simulation program for predicting tractor field performance. *World Applied Sciences Journal*, 2(5): 552

-558.

Aday SH, Najm SI and Hmood MS. 2008. Fuel consumption per unite area and its relation with engine speed and forward speed for the tractor. *Journal of Iraqi Agricultural*, 8(1): 168-180.

Al-Aridhee JKZ. 2011. Effect of tractor's type, speed and tillage depth in some technical indicators of machine unit's and physical characteristics of the soil. M.Sc. Thesis, Department of Agricultural Machines and Equipment, College of Agriculture, University of Baghdad, Iraq, 32-34.

Al-Janobi AA. 2000. Data-acquisition system to monitor performance of fully mounted implement. *Journal of Agricultural Engineering Research*, 75(2): 167-175.

Awady MN. 1987. Agricultural tractors. Text book., College of Agriculture, Ain Shams University (In Arabic). 100 p.

Hilal AAA. 2010. Study the effect of weight of mechanization unit in the amount of soil compaction to three levels speeds and two levels of moisture. Doctoral dissection, Department of Agricultural Machines and Equipment, College of Agriculture, University of Baghdad, Iraq.

Jabour HA. 2010. Studying of effect and interference soil moisture and plowing depth on the drag force resistance and total economic costs for machinery unit. *Al-Taqani Journal*, 23(2): 81-91.

Jebur HA. 2015. Evaluation performance of transport vehicle on different surfaces. *International Journal of Engineering Sciences and Research Technology*, 4(10): 228-233.

Jebur HA. 2016. Determination and analysis of gross power losses for the farm tractor using prediction equations during field operations. *Elixir International Journal*, 99: 43208-43215.

Kassar FH. 2011. The effect of sowing speeds traveling gang angle of disc harrow range and tillage depth on some of the technical parameters for the machine unite furrow dimensions. M.Sc. diss, Department of Agricultural Machines and Equipment, College of Agriculture, University of Baghdad, Iraq.

Khader KAA. 2008. Effect of some primary tillage implement on soil pulverization and specific energy. *Misr Journal of Agricultural Engineering*, 25(3): 731-745.

Khalilian A, Garner HT, Musen HL, Dodd RB and Hale SA. 1988. Energy for conservation tillage in coastal. Plain soil. *Transaction of the ASAE*, 31(5): 1333-1337.

Khorshid FF. 2016. Effect of Soil moisture content and tillage depth on tractor performance with using mold-board plow in silty-clay soil. *Journal of Zankoy Sulaimani*, 18- 1: 221-226.

Liljedahl JB, Turnquist PK, Smith DW, Walter MC and Hoki M. 1989. Tractor and their power units. 4th edition., AVI book, Published by Van Nostrand Reinhold, New York, USA. 240 p.

Macmillan RH. 2002. The mechanics of tractor-implement performance: a textbook for students and engineers. 83 p.

Madlol KM and Jebur HA. 2014. The effect of harrowing type and drill seeders speed and seeding depth in some performance indicators of grain drill stegsted with new Holland 80-66S tractor. *Journal of Iraqi Agricultural*, 19(3): 137-146.

Mayfield W, Hines GS and Roberts L. 1981. A new method for estimating farm machinery costs. *Transactions of the ASAE. American Society of Agricultural Engineers*, 24(5): 1446-1448.

Sharma DN and Mukesh S. 2010. Design of agricul-

tural tractor (principles and problems). 1st ed. Published by Shri Sunil Kumar Jain for Jain Brothers, New Delhi 199 – 213 p.

Wulfsohn D. 1988. Tractive characteristics of radial ply and bias ply tyres in California soil. *Journal of Terramechanics*, 25(2): 111-134.

Younis SM and EL-Said RE. 2009. Tractors and agricultural machinery. A textbook for students, Published by Orchard Knowledge Library. Department of Agricultural Engineering, Faculty of Agriculture, University of Alexandria. 165-171 p.

Younis SM, Elashry EL, SR, Bahnasy AF and Elsybaee IM. 2010. Development a local system for measuring tractors performance. *Misr Journal of Agricultural Engineering*, 27(1): 34-53.

Zedan BA. 2006. Effect of some tillage systems, tillage depths and tractor speed on some performance parameters, soil physical properties and production of Indian pea crop (*vigna radiate L.*). M.Sc. Thesis., Department of Agricultural Machines and Equipment, College of Agriculture, University of Baghdad. 41 p.

Zoz F and Grisso RD. 2003. Traction and tractor performance. ASAE distinguished lecture series. American Society of Agricultural Engineers. 46 p.

Submit your articles online at ecologyresearch.info

Advantages

- **Easy online submission**
- **Complete Peer review**
- **Affordable Charges**
- **Quick processing**
- **Extensive indexing**
- **You retain your copyright**

submit@ecologyresearch.info
www.ecologyresearch.info/Submit.php